



TDS
SMOG DOCTOR TL C3 5W40

Application:

SMOG DOCTOR TL C3 5W40 Top quality, fully synthetic engine oil with reduced ash content thanks to the use of the MIDSAPS formula. Designed for gasoline and Diesel engines working in various conditions. Provides full protection of the engine and associated components in all conditions of engine of passenger car and vans, in which the manufacturer allowed to use oils of this quality class. Recommended for use in engines equipped with DPF -diesel particulate filter, TWC-three-way catalyst. It helps to reduce environmental harmful compounds, minimalizing fuel consumption, without lowering the engine's power. Recommended for vehicles that meet the requirements of Euro 6 standards

Specifications and Standards:

viscosity grade SAE: 5W40

Quality class API: SN

Quality class ACEA: C3

Recommended to: BMW Longlife 04, MB 229.31, MB 229.5, VW 502.00/505.00/505.01,
Renault RN 0700/0710, GM DEXOS 2, PORSCHE A40

Typical physico-chemical attributes

SMOG DOCTOR TL C3 5W40	Typical value
Kinematic Viscosity Index at 100 °C, mm ² /s	14,1
Viscosity Index	170
TBN (mg KOH/g)	8,5
HTHS(cP)@150°C	3,9
Pour Point, °C	-42
Flash Point, °C	230