



TDS
SMOG DOCTOR VL 0W30

Application:

SMOG DOCTOR VL 0W30

Motor oil which meets the requirements of the distinguished manufacturers of vehicles and machines. The relevant composition of base stocks and functional additives in conjunction with the use of ACTIVE POWER technology guarantees engine protection and greatly extends the drain intervals. It keeps the engine clean and improves the engine cold start at subzero temperatures. It is primarily designed for use in engines passenger cars, light commercial vehicles and SUV's. Ready to be mixed with other branded motor oils of this kind.

Specifications and Standards:

viscosity grade SAE: 0W30

Quality class API: SN/CF

Quality class ACEA: C2

Recommended to: BMW Longlife-12FE; MB-Freigabe 229.61; Chrysler MS-13340
Fiat 9.55535-DS1, Fiat 9.55535-GS1; IVECO 18-1811 CLASSE SC1 LV
Jaguar Land Rover STJLR.03.5007; PSA B71 2290, PSA B71 2312

Typical physico-chemical attributes

SMOG DOCTOR TL C2/C3 5W30	Typical value
Kinematic Viscosity Index at 100 °C, mm ² /s	10.98
Viscosity Index	172
TBN (mg KOH/g)	8.2
CCS (@-35°C) cP	4500
Pour Point, °C	-42
Flash Point, °C	234